

PP CORRUGATED TUBE - SINGLE WALL CLOSED

PART NR.

See dimensions table

COUNTRY OF ORIGIN

China

STANDARDS

REACH and RoHS compliant

CHARACTERISTICS

- Flexible and flame-retardant polypropylene tube
- Suitable for insulation use in automotive electronics, with excellent electrical and physical properties, including excellent acid fastness and corrosion resistance
- Great shape permanence to heat and enormous cold impact strength
- Bending stable
- Excellent chemical resistance

PHOTO / TECHNICAL DRAWING



DIMENSIONS

Part nr.	Nominal size	Inner Ø mm	Outer Ø mm	Mtrs/reel
CCT06-100	6,0	6,0 ± 0,3	9,0 ± 0,3	100
CCTE06-100	6,5	6,0 ± 0,3	9,0 ± 0,3	100
CCT07-100	7,0	7,0 ± 0,3	10,0 ± 0,3	100
CCT09-100	9,0	9,0 ± 0,3	13,0 ± 0,3	100
CCTE09-100	9,0	9,0 ± 0,3	13,0 ± 0,3	100
CCT10-100	10,0	10,0 ± 0,3	14,0 ± 0,3	100
CCT11-100	11,0	11,0 ± 0,3	15,0 ± 0,3	100
CCTE11-100	11,0	11,0 ± 0,3	15,0 ± 0,3	100
CCT12-100	12,0	12,0 ± 0,3	16,0 ± 0,3	100
CCT13-100	13,0	13,0 ± 0,3	17,0 ± 0,3	100
CCTE13-100	13,0	13,0 ± 0,3	17,0 ± 0,3	100
CCT16-050	16,0	16,0 ± 0,3	20,0 ± 0,3	50
CCTE16-050	16,0	16,0 ± 0,3	20,0 ± 0,3	50
CCT19-050	19,0	19,0 ± 0,3	23,0 ± 0,3	50
CCTE19-050	19,0	19,0 ± 0,3	23,0 ± 0,3	50
CCTE20-100	20,0	20,0 ± 0,3	24,0 ± 0,3	100
CCTE20-025	20,0	20,0 ± 0,3	24,0 ± 0,3	25

Part nr.	Nominal size	Inner Ø mm	Outer Ø mm	Mtrs/reel
CCT22-025	20,0	22,0 ± 0,3	27,0 ± 0,3	25
CCT23-025	23,0	23,0 ± 0,3	28,0 ± 0,3	25
CCT25-025	25,0	25,0 ± 0,3	30,0 ± 0,3	25
CCTE25-025	25,0	25,0 ± 0,3	30,0 ± 0,3	25
CCT26-025	26,0	26,0 ± 0,3	31,0 ± 0,3	25
CCT28-025	28,0	28,0 ± 0,3	34,0 ± 0,3	25
CCTE28-050	28,0	28,0 ± 0,3	34,0 ± 0,3	50
CCTE28-025	28,0	28,0 ± 0,3	34,0 ± 0,3	25
CCT30-025	30,0	30,0 ± 0,3	36,0 ± 0,3	25
CCTE30-050	30,0	30,0 ± 0,3	36,0 ± 0,3	50
CCTE30-025	30,0	30,0 ± 0,3	36,0 ± 0,3	25
CCT32-025	32,0	32,0 ± 0,3	38,0 ± 0,3	25
CCTE32-050	32,0	32,0 ± 0,3	38,0 ± 0,3	50
CCTE32-025	32,0	32,0 ± 0,3	38,0 ± 0,3	25
CCT35-025	35,0	35,0 ± 0,3	40,0 ± 0,3	25
CCTE35-050	35,0	35,0 ± 0,3	40,0 ± 0,3	50
CCTE35-025	35,0	35,0 ± 0,3	40,0 ± 0,3	25
CCT40-025	40,0	40,0 ± 0,3	45,0 ± 0,3	25

TECHNICAL SPECIFICATIONS

Material:

Temperature range:

PP, black or orange

-40 ~ 135 °C