## japOTO CARTRIDGE FUSE - JM SERIES

PART NR.
See rating table

COUNTRY OF ORIGIN
Japan

STANDARDS
REACH and RoHS compliant
ISO 8820-4
JASO D612

## **CHARACTERISTICS**

- Meets international specs, complies to ISO 8820-4, JASO D612 and other standards
- Element visibility from top through transparent cover
- Robust/sturdy body construction
- Self extinguishing, color coded body materials
- High temperature resistive plastics used for fuse body materials
- Secure and controlled time-delayed functioning with purpose designed elements
- Integrated, endurable, Cu alloy receptacles
- Used in Japanese, European, American and Korean designed vehicles

**PHOTO / TECHNICAL DRAWING** 



Section A - A

A

1 - cover
2 - housing
3 - element

**DIMENSIONS** 

L x W x H:

14,1 x 12 x 15,9 mm

**RATING TABLE** 

Part nr.	Color	Rating (A)	Rating (V)
CBF015JM	grey	15	32
CBF020JM	light blue	20	32
CBF025JM	white	25	32
CBF030JM	pink	30	32
CBF040JM	green	40	32

TECHNICAL SPECIFICATIONS

Body: PA66, color coded Cover: PAR, transparent Receptacles: Copper alloy

www.ae-industries.nl