

PART NR.
THKS13P001FCO

COUNTRY OF ORIGIN
Poland

STANDARDS
REACH and RoHS compliant
ISO 11446

CHARACTERISTICS

- With fog light cut-off
- Supplied with:
 - waterproof cap
 - fasteners & clips
 - flexible rubber gasket

PHOTO / TECHNICAL DRAWING



DIMENSIONS

TECHNICAL SPECIFICATIONS

ISO 11446
13-pin, 12 Volt

Power supply
(steady plus)
orange, wire 2,5 mm²


Power supply
(switched with an ignition switch)
grey, wire 2,5 mm²

Rear fog light
blue, wire 1,5 mm²

Common return
(for electric circuit contact no. 10)
black/white, wire 2,5 mm²

Trailer detection, wire 1,5 mm²
(in the socket, contact no. 12 is
connected with contact no. 3
to report to the towing vehicle
whether a trailer is connected)

Reverse light
pink, wire 1,5 mm²



Common return
(for electric circuit contact no. 1-8)
white, wire 2,5 mm²

Left-hand taillight, position light,
marker lights and licence plate
light
black, wire 1,5 mm²

Left-hand direction indicator light
yellow, wire 1,5 mm²

Stop lights
red, wire 1,5 mm²

Right-hand direction indicator light
green, wire 1,5 mm²

Right-hand taillight, position
light, marker lights and licence
plate light
brown, wire 1,5 mm²

Common return
(for electric circuit contact no. 9)
white/red, wire 2,5 mm²

Strands: 12 x 0,5 mm²
1 x 0,75 mm²
Length: 1,5 m

Max. electrical current: 12V