

MULTI-CORE CABLE (H05VV-F) - ROUND

PART NR.

See dimensions table

COUNTRY OF ORIGIN:

Poland

STANDARDS:

REACH and RoHS compliant

PN-EN 60228

PN-EN-50525-2-11

CHARACTERISTICS:

- General purpose conductor cable
- Manufactured according to harmonized norm (H) at rated voltage 300/500V (05) with polivinyl chloride insulation (VV) and stranded copper wire (F)

PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Conductor:	Copper wire (Class 5)
Insulation:	PVC T12
Bending radius:	4 x D
Outer insulation:	PVC TM2
Test voltage:	2000V
Rated voltage:	300/500V
Temperature rating:	-40 °C ~ 70 °C

DIMENSIONS

Reel							
Part nr. without trace color	Wire size mm ²	Number of cores	Outer cable Ø (mm)	Nominal coating thickness (mm)	Nominal insulation thickness (mm)	Color coating	Mtrs/reel
W706201501-10	1,50	2	7,3	0,8	0,7	black	10
W706301501-10	1,50	3	7,9	0,9	0,7	black	10
W706401501-10	1,50	4	8,9	1,0	0,7	black	10
W706501501-10	1,50	5	9,9	1,1	0,7	black	10
W706701501-10	1,50	7	10,8	1,2	0,7	black	10
W706801501-10	1,50	8	11,6	1,2	0,7	black	10