

PART NR.

See dimensions table

COUNTRY OF ORIGIN:

Italy

STANDARDS:

REACH and RoHS compliant

EN 60228 – EN 50525 (2x 0,5 mm²)

EN 50525 (2x 0,75, 2x 1,00, 2x 1,50 and 2x 2,50 mm²)

CEI 20-20 / CEI 20-29 (2x 4,00 mm²)

PHOTO / TECHNICAL DRAWING



DIMENSIONS

Part nr.	Wire size mm ²	Nominal conductor construction (wires x mm ²)	Max. conductor resistance (Ohm/km)	Outer cable (mm)	Min. insulation thickness (mm)	Core color		Mtrs/spool
						black	red	
LS2X0050ZR100SP	2 x 0,50	16 x 0,20	39,00	1,9 x 3,9	0,5	Z	R	100
LS2X0075ZR100SP	2 x 0,75	24 x 0,20	26,00	2,2 x 4,5	0,5	Z	R	100
LS2X0100ZR100SP	2 x 1,00	32 x 0,20	19,50	2,5 x 5,2	0,6	Z	R	100
LS2X0150ZR100SP	2 x 1,50	30 x 0,25	13,30	2,9 x 6,0	0,6	Z	R	100
LS2X0250ZR100SP	2 x 2,50	50 x 0,25	7,60	3,6 x 7,4	0,7	Z	R	100
LS2X0400ZR100SP	2 x 4,00	56 x 0,25	4,95	4,1 x 8,6	0,7	Z	R	100

TECHNICAL SPECIFICATIONS

Conductor: Electrolytic red copper CU ETP 1
 Insulation: PVC type TM2
 Max. operating voltage: 300V
 Temperature rating: -15 °C ~ 70 °C